

TG5395 HST

Dimensions: [US](#) | [METRIC](#)

 [Print Specifications](#)



Power

Engine	Diesel, 3 cylinder, water cooled
Displacement	1498cc
Power	37hp at 2600rpm
Fuel Capacity	8.8 gal
No of Cylinders	3

Transmission (Hydro)

Type	3 Range Hydrostatic with Servo Control
Cruise control	Standard
Speed	0.23 - 19.2mph

Transmission (IQ)

Type	IQ - electrohydraulic control
Gears forward/reverse	12/12
Speed	0.23 - 19.2mph

Brakes

Type	Wet discs
------	-----------

Tyres

Front	212/80D-15 (turf) 7-16 (agri), 8-16 (wide agri)
Rear	355/80D-20 (turf) 12.40 - 24 (agri), 13.6 - 24 (wide agri)

PTO

Engagement	Soft start and standard
Mid PTO	1916 PTO rpm @ 2430 rpm
Rear PTO	540 PTO rpm @ 2430 rpm, 1000 PTO rpm @ 2500 rpm

Hydraulics

Steering	Hydrostatic
Main System	Engine mounted gear pump
Max Output at Engine rpm	5.2gal/min at 2600 rpm
Three Point Lift	Category 1
Lift Capacity	2,800 lb at ball ends

Electrical Equipment

Alternator	60 amp
------------	--------

Dimensions (ROPS model)

Width	59 ins., 55.5 ins. on narrow ag tyres / 56.7 ins. on turf tyres
Length	123.6 in. including front hitch
Height	101 in. on narrow ag tyres, 102.2 in. on wide ag tyres, 99.6 in. on turf tyres
Weight	29,92lbs

Ground clearance	Minimum 12 in. on turf tyres
Wheelbase	69.7 in.