

TM3265

Dimensions: [US](#) | [METRIC](#)

 [Print Specifications](#)



Power

Engine	Diesel, indirect injection, overhead valve
Displacement	1498cc
Power	18.9kw at 2500rpm
Fuel Capacity	28 litres
No of Cylinders	3

Transmission

Drive Wheels	4WD
Driving Speed	Hydro: 1.7-22.2kph, Mech: 0-22.2kph
No. of Speeds	3 Hydro, 8 Mech
Differential Lock	STD

Brakes

Type	Wet discs
------	-----------

Tyres

Front	Agri front 6-12, Turf front 24x10.50-12
Rear	Agri rear 9.5-18, Turf rear 315/75D-15

PTO

Shaft	Hydro: 3.49cm 6-spline, Mech: 3.49cm 6-spline
Rear Speed	Hydro: 567 @ 2600 rpm. Mech: 571 @ 2600 rpm
Front Speed	Hydro: 2032 @ 2600 rpm. Mech: 2129 @ 2600 rpm

Hydraulics

Lift Capacity	600 kg
Position Control	Standard
Pump Capacity Main	(l/min): 20.1
Rear Linkage Type	Category 1

Dimensions

Length	2.87m
Weight	HST: 820kg, Mech: 830kg
Ground Clearance	0.23m