

TH4335 Mechanical

Dimensions: [US](#) | [METRIC](#)

 [Print Specifications](#)



Engine

Model	E3CD
Displacement	1498 cc
No. of Cylinders	3
Net Output	23.5 kW
Rated Speed	2600 rpm
Fuel Capacity	35 litres

Drive Train

Synchro Shuttle	Standard
Number of Speeds	12 forward / 12 reverse
Main Clutch	Dry Single
Creep Gears	OPT
Travelling Speed	Forward: 28 km/h Reverse: 22 km/h
Diff Lock	Standard

PTO

Engagement	Independent, electro-hydraulic clutch
Mid PTO	2080 rpm
Rear PTO	565 / 1135 rpm

Hydraulics

3P Linkage	Cat 1
Lift Capacity - Link End	1100 kg
Position Control	Standard
Pump Capacity Main	32.1 litres/min
Pump Capacity Sub	13.6 litres/min
Auxiliary Valves	Standard (x2)
Joystick Valve	OPT

Dimensions

Overall Length	3150 mm
Overall Width	1130 mm
Overall Height	2420 mm
Weight	1160 kg
Wheel Base	1695 mm
Tread Front	875 mm
Tread Rear	900 mm

Other Specifications

Brake	Wet disk, 2 pedal
Steering System	Power steering
Rear Hitch	STD
ROPS	Rear, folding
Mowerdeck	OPT (1524 mm)

